




China 608 Bearing Supplier



6214 2RS - O&Kai Z1V1 Z2V2 Z3V3 Deep Groove Ball Bearing SKF NSK NTN NACHI Koyo FAG OEM

Bearing No. 6214

6214 Bearing 2D drawings and 3D CAD models

Size	70x125x24 mm
Bore Diameter	70 mm
Outer Diameter	125 mm
Width	24 mm
d	70 mm
D	125 mm
B	24 mm
C	24 mm
r min.	1.5 mm
da min.	79 mm
Da max.	116 mm
ra max.	1.5 mm
Weight	1.07 Kg
Basic dynamic load rating (C)	62 kN
Basic static load rating (C0)	44 kN
(Grease) Lubrication Speed	5000 r/min
Category	Single Row Ball Bearings
Inventory	0.0
Manufacturer Name	NACHI
Minimum Buy Quantity	N/A
Weight / Kilogram	0
Product Group	B00308
Enclosure	Open
Precision Class	ABEC 1 ISO P0



China 608 Bearing Supplier

Maximum Capacity / Filling Slot	No
Rolling Element	Ball Bearing
Snap Ring	No
Internal Special Features	No
Cage Material	Steel
Internal Clearance	C0-Medium
Inch - Metric	Metric
Long Description	70MM Bore; 125MM Outside Diameter; 24MM Outer Race Width; Open; Ball Bearing; ABEC 1 ISO P0; No Filling Slot; No Snap Ring; No Internal Special Features; C0-Medium Internal Clearance; Steel Cage
Other Features	Deep Groove
Category	Single Row Ball Bearing
UNSPSC	31171504
Harmonized Tariff Code	8482.10.50.68
Noun	Bearing
Keyword String	Ball
Manufacturer URL	http://www.nachiamerica.com
Outside Diameter	4.921 Inch 125 Millimeter
Bore	2.756 Inch 70 Millimeter
Outer Race Width	0.945 Inch 24 Millimeter
Inner Race Width	0 Inch 0 Millimeter
Bore Type	Cylindrical Bore
Configuration	Single Row
Bore Size	70 mm
Width	24 mm
Fillet Radius/Chamfer	1.5 mm
Dynamic Load Rating	62,000 N



China 608 Bearing Supplier

Static Load Rating	44,000 N
Limiting Speed - Grease	5,100 rpm
Limiting Speed - Oil	6,300 rpm
Factor fo	14.4
Radial Clearance	0.010 to 0.030 mm
da (min)	79 mm
Da (max)	116 mm
ra (max)	1.5 mm